



BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		INITIAL RELEASE	2008.11.03	A.0



PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
9	9
10	10
11	11
12	12
13	13
11	11
17	17
18	18
19	19
20	20
21	21
19	19
23	23
24	24
22	22
6	6
7	7
14	14
15	15
16	16
D+B SHELL SHELL	



- NOTES:
- ELECTRICAL PROPERTIES:
    - 100% OPEN AND SHORT TEST
    - CONDUCTOR RESISTANCE: 5 OHMS
    - INSULATION RESISTANCE: 10 MEGOHMS
    - HI-POT: DC300V/0.01S
    - 100% HDTV, BLUE RAY DVD TEST(1080P:UP TO 7M); (1080I: 10M,15M)
    - ALL CABLE PRODUCTION PROCESS ARE CONTROLLED BY ATC TEST DEVICE.
  - ALL MATERIAL BE RoHS COMPLIANT.

NO.	PARTS NAME	Q'TY	SPECIFICATION
⑦	TAG	1PCS	DELTACO TAG
⑥	CORE MOLD	2PCS	BLACK PVC
⑤	CORE	2PCS	OD*ID*L: 14.3*9.0*28.5mm
④	SCREW	2PCS	#4-40 UNC, HOOD MOLDED: WHITE PVC
③	HOOD MOLD	2PCS	BLACK PVC
②	DVI(24+1)M	2PCS	GOLD PLATED SHELL
①	CABLE	1PCS	(30AWG*1P+D+FAM)*7+28AWG*1P+28AWG*3C+AEB OD:8.6mm BLACK PVC JACKET

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	DVI-600
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:  
DVI(24+1)/M-DVI(24+1)/M